

Classification of llaza solar protection systems for CE marking in accordance with regulation UNE-EN13561:2004 + A1:2009



LLAZA-SPLENBOX RANGE

PROJECTION (m)	SPLENBOX 300	WIDTH (m)					
		2.5	3	3.5	4	4.5	5
1.25							
1.50							
1.75							
2.00							
2.25							
2.50							
2.75							
3.00							

PROJECTION (m)	SPLENBOX 400	WIDTH (m)							
		2.5	3	3.5	4	4.5	5	5.5	6
2.00									
2.50									
3.00									
3.25									
3.50									
3.75									
4.00									

LLAZA-MATIC RANGE

PROJECTION (m)	MATICBOX 350	WIDTH (m)					
		2.5	3	3.5	4	4.5	5
2.00							
2.50							
3.00							
3.25							
3.50							

PROJECTION (m)	MONOBOX 400	WIDTH (m)							
		2.5	3	3.5	4	4.5	5	5.5	6
2.00									
2.50									
3.00									
3.25									
3.50									
3.75									
4.00									

Excluding types

CLASS I

CLASS II

CLASS III

CLASS II for
CROSSED ARMS

CLASS III for
CROSSED ARMS

EN13561 CLASSES	WIND RESISTANCE
CLASS I	28 Km/h.
CLASS II	38 Km/h.
CLASS III	49 Km/h.

LLAZA-WIN RANGE

PROJECTION (m)	WINBOX	WIDTH (m)							
		2.5	3	3.5	4	4.5	5	5.5	6
1.50									
2.00									
2.50									
3.00									
3.50									

PROJECTION (m)	WIN-MONOBLOC WIN-MNB TEXPRO	WIDTH (m)									
		2.5	3	3.5	4	4.5	5	5.5	6	6.5	7
1.50											
2.00											
2.50											
3.00											
3.50											
4.00											

LLAZA-BOX RANGE

PROJECTION (m)	MICROBOX 300	WIDTH (m)							
		1.5	2	2.5	3	3.5	4	4.5	5
0.70									
0.80									
1.00									
1.20									
1.40									
1.60									

PROJECTION (m)	STORBOX 250	WIDTH (m)					
		2	2.5	3	3.5	4	4.5
1.25							
1.50							
1.75							
2.00							
2.25							
2.50							


PROJECTION (m)	STORBOX 300	WIDTH (m)								
		2	2.5	3	3.5	4	4.5	5	5.5	6
1.50										
1.75										
2.00										
2.25										
2.50										
2.75										
3.00										

PROJECTION (m)	MAXIBOX 300	WIDTH (m)							
		2.5	3	3.5	4	4.5	5	5.5	6
1.50									
1.75									
2.00									
2.25									
2.50									
2.75									
3.00									


Excluding types
 CLASS I
 CLASS II
 CLASS III
 CLASS II for CROSSED ARMS
 CLASS III for CROSSED ARMS


EN13561 CLASSES	WIND RESISTANCE
CLASS I	28 Km/h.
CLASS II	38 Km/h.
CLASS III	49 Km/h.


LLAZA-BOX RANGE


	TEXPRO-SYSTEM		WIDTH (m)							
	PROJECTION (m)		2	2.5	3	3.5	4	4.5	5	5.5
	1.50									
	1.75									
	2.00									
	2.25									
	2.50									
	2.75									
	3.00									

LLAZA-ART RANGE

	ART 250		WIDTH (m)				
	PROJECTION (m)		2	2.5	3	3.5	4
	1.25						
	1.50						
	1.75						
	2.00						
	2.25						
	2.50						

	COMPLET 07 COMPLET TEXPRO 07		WIDTH (m)									
	PROJECTION (m)		1.5	2	2.5	3	3.5	4	4.5	5	5.5	6
	1.50											
	1.75											
	2.00											
	2.25											
	2.50											
	2.75											
	3.00											
	3.25											


	ART MNB 350		WIDTH (m)									
	PROJECTION (m)		1.5	2	2.5	3	3.5	4	4.5	5	5.5	6
	1.50											
	1.75											
	2.00											
	2.25											
	2.50											
	2.75											
	3.00											
	3.25											
	3.50											

 Excluding types

 CLASS I

 CLASS II

 CLASS III

 CLASS II for
CROSSED ARMS

 CLASS III for
CROSSED ARMS

EN13561 CLASSES	WIND RESISTANCE
CLASS I	28 Km/h.
CLASS II	38 Km/h.
CLASS III	49 Km/h.